

# Texsteam™ 5000 Series Pump CE Mark

Texsteam™ is pleased to announce that our 5000 Series pump is now CE marked, declaring that it guarantees the product's conformity to EU health, safety, and environmental protection standards.



Figure 1: TXT 5000 Series Pump

Plunger Size	Maximum Discharge Pressure		Maximum Volume Output Gallons (Liter) per Day
	psi	(bar)	
1/4"	10,000	(690)	16 (60.5)
3/8"	10,000	(690)	43 (162.7)
1/2"	10,000	(690)	85 (322)
3/4"	5,000	(344)	160 (605.7)
1"	3,000	(206)	320 (1,211)
1-1/4"	2,000	(138)	500 (1,892.7)

The product is in conformity with the relevant union harmonization legislation:

- Machinery Directive 2006/42/EC
  - Pressure Equipment Directive 2014/68/EU
- Designed for continuous operation
  - Excellent for pumping chemicals, methanol, and corrosion inhibitors
  - Field adjustable speed/volume control
  - Simple modification can lower pumping rate to one stroke every five minutes
  - Operates with air/gas pressures as low as 15 psi
  - Trim for corrosive applications available
  - Microswitch design available
  - Regulator, gauges and tanks available as accessories

Please consult your local Channel Partner listed below for more details

*Natural Gas Solutions North America, LLC General Terms & Conditions for Sale of Products, Parts and Services, dated October 1, 2018 REV 5-15-2020, apply to orders unless otherwise negotiated*